XPGUB9-64G5 1/3



PRODUCT-DETAILS

XPGUB9-64G5 XP HSING THRDGLASS CVR 7IN DIA



General Information	
Extended Product Type	XPGUB9-64G5
Product ID	7TAA137500R0040
EAN	5415022409994
Catalog Description	XP HSING THRDGLASS CVR 7IN DIA
Long Description	Explosionproof Meter Housing in Hazardous Locations, Threaded Glass Cover, Conduit Size 2-1/2 Inches, Cover Opening Diameter 6-7/8 Inches, Inside Dimensions: Diameter 6-5/8 Inches, Depth 3-5/16 Inches, cULus, UL Listed, CSA, Approved for Class I, Divisions 1, 2, Groups B, C, D, Class II, Divisions 1, 2, Groups E, F, G Locations, Copper-Free Aluminum with Stainless Steel Hardware

Application	Provide Reliable Protection for Measurement and Detection Equipment with Applications in Hazardous and Adverse Environments
Product Type	Explosionproof Instrument Housing
Ordering	
EAN	5415022409994
UPC	78621012899

XPGUB9-64G5 2/3

Technical	
Mounting Type	Four 3/8 Inch Mounting Holes
Number of Batteries	
Color	Metallic
Material	Copper-Free Aluminum Body and Cover; Aluminum Mounting Plate; Neoprene Gasket; Stainless Steel Hardware
Size	Width 7-15/16 Inch, Depth 7-15/16 Inch, Height 5-3/4 Inch
<u>Environmental</u>	
WEEE Category	Product Not in WEEE Scope
Container Information	
Package Level 1 Units	1 EA
Package Level 1 Height	525.526 mm 20.69 in
Package Level 1 Depth / Length	914.4 mm 36 in
Package Level 1 Width	1082.802 mm 42.63 in
Certificates and Declarations	
Data Sheet, Technical Information	XPGUB9-64G5
Instructions and Manuals	XPGUB9-64G5
Classifications	
ETIM 8	EC002503 - Explosion proof enclosure/housing
UNSPSC	39121314

Categories

 $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Installation\ Products\ \rightarrow\ Cable\ Protection,\ Explosion\ Proof\ and\ Lighting\ \rightarrow\ Hazardous\ Lighting\ \&\ Enclosures$

XPGUB9-64G5 3/3

