
FB3D24 1/3



PRODUCT-DETAILS

FB3D24

FLEXIBLE BRAID 230.4KCMIL 24IN LONG



General Information	
Extended Product Type	FB3D24
Product ID	7TAA140140R0001
Catalog Description	FLEXIBLE BRAID 230.4KCMIL 24IN LONG
Long Description	Flexible Braids for Grounding, 230.4 kcmil, Bolt Hole 7/16, 24 Inch Length, Number of Braids in Ferrule 3

Ordering	
UPC	75114432955
Country of Origin	United States (US)
Selling Unit of Measure	each

Container Information	
Package Level 1 Units	10 EA
Package Level 1 Width	133.35 mm 5.25 in
Package Level 1 Height	136.398 mm 5.37 in

FB3D24 2/3

Package Level 1 Depth / 609.6 mm Length 24 in

Additional Information	
Application	Flexible Copper Braids for use in Substation and Grounding Applications
Brand / Label	Homac
Cable Length	24 in
Conductor Category	Flexible
Conductor Shape	Flat
Effective Date	20220509
Material of Conductor	Tin-Plated Copper
Product Main Type	BOREAL FLEXIBLE BRAID CONNECTORS
Product Name	Terminals, electrical splices and electrical couplings; wafer probers
Product Type	Flexible Braid Connector - 1-Hole
Special Functions	Tin-Plated Copper Braids and Ferrules for High Conductivity and Corrosion Resistance. Enables Linear Expansion, Equipment Vibration and Offset Connections.
Standards	UL E3060, CSA LR29625

Certificates and Declarations

Data Sheet, Technical FB3D24 Information

Classifications	
ETIM 6	EC000839 - Braid wire
ETIM 7	EC000839 - Braid wire
UNSPSC	39121465
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4695 >> Flexible braid

Categories

 $Low\ Voltage\ Products\ \rightarrow\ Installation\ Products\ \rightarrow\ Cable\ Accessories\ and\ Apparatus\ \rightarrow\ Distribution\ Connectors$

FB3D24 3/3

