




 PRODUCT-DETAILS

R43HXXEBX2BXXSYS15A

MVR, 38KV, 3PH, TRIP SINGLE, 170KV



General Information

Extended Product Type	R43HXXEBX2BXXSYS15A
Product ID	7TAA201250R0045
Catalog Description	MVR, 38KV, 3PH, TRIP SINGLE, 170KV
Long Description	Molded Vacuum Recloser, Triple Single Phase, 38kV, Horizontal Mounting Frame, No Control Transformers (customer supplied), Control Model - 651R Customer Special, 20 Foot Control Cable Standard Type, No Source Side Voltage Sensing, Terminal Lugs - NEMA 2-Hole Lug, Has Both Line and Load Side Arresters Brackets, No Surge Arresters, No Wildlife Protectors, Position Indicator - Standard (Green Open, Red Closed), Ships Completely Assembled and Site Ready

Ordering

UPC	75114344852
Country of Origin	United States (US)
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 EA
Package Level 1 Width	25.4 mm 1 in
Package Level 1 Height	25.4 mm 1 in
Package Level 1 Depth / Length	25.4 mm 1 in

Additional Information

Application	Triple-Single (3 - Single)
Brand / Label	Elastimold
Current Rating	800 A
Effective Date	20170629
Mounting Type	Horizontal Mounting
Process Temperature Rating	Normal -10 to +45 °C Extreme -40 to +65 °C
Product Name	Other
Product Type	Molded Vacuum Recloser
Standards	ANSI C37.60-2003
Voltage Rating	38 kV

Certificates and Declarations

Data Sheet, Technical Information	R43HXXXEBX2BXXSYS15A
-----------------------------------	----------------------

Classifications

UNSPSC	39121570
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4783 >> Recloser

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Overhead Apparatus

