WRS352 1/3



PRODUCT-DETAILS

WRS352

COMP STIRRUP W/CNTX 4/0-3/0ASCR 2SD



General Information	
Extended Product Type	WRS352
Product ID	7TAA267120R0021
Catalog Description	COMP STIRRUP W/CNTX 4/0-3/0ASCR 2SD
Aluminum Compression H-Tap Connector with Tin Plated Copper Stirrup, ong Description Filled, Wire Range: 4/0-3/0 ASCR, 4/0 Stranded -3/0 Stranded AWG, Stirrup # Copper, Wing Shaped, 2 H-Tap Connectors on Stirrup. 10 inch x 2-15/1	

Ordering	
UPC	783786051694
Country of Origin	Mexico (MX)
Selling Unit of Measure	each

Container Information	
Package Level 1 Units	1 EA
Package Level 1 Width	0 mm
	0 in

WRS352 2/3

Package Level 1 Height	0 mm
	0 in
Package Level 1 Depth /	0 mm
Length	0 in
Package Level 2 Units	25 EA
Package Level 2 Width	285.75 mm
	11.25 in
Package Level 2 Height	158.75 mm
	6.25 in
Package Level 2 Depth /	311.15 mm
Length	12.25 in
Package Level 3 Units	2100 EA
Package Level 3 Width	0 mm
	0 in
Package Level 3 Height	0 mm
-	0 in
Package Level 3 Depth /	0 mm
Length	0 in

Additional Information	
Application	Protect Main Conductors from Arcing Damage.
Brand / Label	Blackburn
Connection Type	Compression
Effective Date	19991027
Insulation Material	None
Material	Aluminum with Tin Plated Copper Bails
Product Name	"TERMINALS, ELECTRICAL SPLICES"
Product Type	Compression Connector with Stirrup
Size	10 X 2-15/16 inches Tall
Special Functions	Guard Main Conductors Against Arcs - Perfect for when Hot Line Taps are Installed. Utilize Standard Wide Range Connectors and Plated Copper Bails for High Conductivity and Corrosion Resistance.
Wire Size	4/0 to 3/0 STR AWG

Certificates and Declarations	
Data Sheet, Technical Information	WRS352

Classifications	
UNSPSC	39121409
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4543 >> Wire connectors

WRS352 3/3

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Cable\ Accessories\ and\ Apparatus \rightarrow Distribution\ Connectors$

