



 PRODUCT-DETAILS

LTC038GY-500

3/8 GY NM LT CONDUIT 500'



General Information

Extended Product Type	LTC038GY-500
Product ID	7TAD012640R0001
EAN	5415022259124
Catalog Description	3/8 GY NM LT CONDUIT 500'
Long Description	Commercial Grade, Type B Liquidtight Flexible PVC Conduit, 3/8 Inch Conduit Size, Approved for Outdoor and Direct Burial in the US, UL Temperature Ratings - 80 Degrees C Dry, 60 Degree C Wet, 70 Degree C Oil, Oil Resistant, Voltage Rating 600V, Gray, 500 Foot Reel

Additional Information

Application	Machine Tools, Motor Hookups, Food Processing Equipment, Extensions from Wire Ways, and Sensor and Micro Switch Wiring Found In Control Consoles.
Product Type	Liquidtight Flexible Non-Metallic Conduit

Ordering

EAN	5415022259124
UPC	785991210804

Dimensions

Product Net Depth / Length	500 ft
----------------------------	--------

Technical

Number of Batteries	0
Color	Gray
Material	PVC
Voltage Rating	600 V

Environmental

WEEE Category	Product Not in WEEE Scope
---------------	---------------------------

Container Information

Package Level 1 Units	500 ft
Package Level 1 Height	457.2 mm 18 in
Package Level 1 Depth / Length	609.6 mm 24 in
Package Level 1 Width	254 mm 10 in

Certificates and Declarations

Data Sheet, Technical Information	TDS000138
Instructions and Manuals	LTC038GY-500

Classifications

ETIM 8	EC001177 - Protective plastic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings

