



PRODUCT-DETAILS

XSL305UNSSTGCA2TI3

XSL3 LED 5KLM 120-277V SS STG CONE KY I3



General Information

Extended Product Type	XSL305UNSSTGCA2TI3
Product ID	7TBA022610R0111
Catalog Description	XSL3 LED 5KLM 120-277V SS STG CONE KY I3
Long Description	Ex-Solutions™ LED , 5 600 lumens, 37W, universal 120-277 VAC 50/60Hz, standard housing with stainless steel inserts, Glass Coating:Anti-shatter teflon coating , thermal shock-resistant globe, cast aluminum guard, 3/4 in. cone-top pendant, Options (light distribution): internal reflector 35° beam angle, Housing Colour: HazCote black custom anti-corrosion coating, Material:aluminum die-cast, HazCote black custom anti-corrosion coating

Additional Information

Product Main Type	Emergency Lighting
Application	Industrial

Ordering

UPC	786210340715
-----	--------------

Dimensions

Product Net Height	16-3/4 in
Product Net Depth / Length	14-7/8 in
Product Net Width	13-3/8 in
Product Net Weight	21 lb

Technical

Mounting Type	Cone Top
Lamp Type	LED
Illuminance	5 600 lm
Number of Batteries	0
	37 W

Environmental

WEEE Category	Product Not in WEEE Scope
---------------	---------------------------

Container Information

Package Level 1 Units	1 EA
Package Level 1 EAN	0786210340715
Package Level 1 Height	0.254 mm 0.01 in
Package Level 1 Depth / Length	0.254 mm 0.01 in
Package Level 1 Width	0.254 mm 0.01 in
Package Level 1 Gross Weight	21.5 lb

Certificates and Declarations

Data Sheet, Technical Information	9AKK108468A2744
Instructions and Manuals	9AKK108468A2745
Declaration of Conformity - CE	No declaration needed
REACH Declaration	No declaration needed

Classifications

UNSPSC	39111612
--------	----------

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Hazardous Lighting & Enclosures

