




---

 PRODUCT-DETAILS

# 12L50-2LD9UP1N3WAD

## 12L50-2LD9-ULTP1N3WAD




---

**General Information**

Extended Product Type	12L50-2LD9UP1N3WAD
Product ID	7TBA134205R0010
Catalog Description	12L50-2LD9-ULTP1N3WAD
Long Description	Pictogram Combination Unit, Battery Type: lead-calcium, single face wall mount (less canopy), 120/347VAC, Voltage DC: 6V, Battery Wattage (W): 50, self-powered, two lamps, Lamp Type: MR16 LED, Lamp Voltage: 12V, Lamp Wattage: 5W, Colour: factory white, diagnostics, audible, Head Style: shielded, Battery Run Time (Minimum): 30 minutes

---

**Additional Information**

Product Main Type	Emergency Lighting
-------------------	--------------------

---

**Ordering**

UPC	787321188005
-----	--------------

---

### Environmental

---

WEEE Category	Product Not in WEEE Scope
---------------	---------------------------

---

---

### Container Information

---

Package Level 1 Units	1 EA
Package Level 1 Height	292.1 mm 11.5 in
Package Level 1 Depth / Length	462.28 mm 18.2 in
Package Level 1 Width	91.44 mm 3.6 in

---

---

### Certificates and Declarations

---

Declaration of Conformity - CE	No declaration needed
--------------------------------	-----------------------

---

---

### Classifications

---

UNSPSC	39111707
--------	----------

---

---

### Categories

---

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Emergency Lighting



