




---

 PRODUCT-DETAILS

# 95MR7G-3.5

## CABLE ASBLY SCDRY FAA STL7




---

**General Information**

Extended Product Type	95MR7G-3.5
Product ID	7TBA136260R0535
Catalog Description	CABLE ASBLY SCDRY FAA STL7
Long Description	Cable Assembly Secondary FAA Style 7 Receptacle, 2/12 AWG (3.3mmsq) Thermoplastic Insulated Waterproof Cable with overall Jacket, Rated 600 Volts Between Contacts, 1500 Volts to Earth, 20 Amps, 90 Degrees Celsius, Outside Diameter 12.7mm (.5 inch), Length 3.5 meters.

---

**Ordering**

UPC	708917328353
Country of Origin	United States (US)
Selling Unit of Measure	each

---

**Container Information**

Package Level 1 Units	1 EA
Package Level 1 Width	25.4 mm

	1 in
Package Level 1 Height	25.4 mm
	1 in
Package Level 1 Depth / Length	25.4 mm
	1 in

### Additional Information

Brand / Label	Amerace
Current Rating	20 A
Effective Date	20091013
Insulation Material	Yes
Product Name	Other
Product Type	Secondary Cable Assembly - Receptacle FAA Style 7
Size	3.5 Meters Long
Standards	ISO 9001, ISO 14001, QMI/SAI Global Certified, CSA Listed, Teflon Wires Certified to UL1199 and CSA1 A/B
Voltage Rating	Between contacts 600 V To earth 1,500 V

### Certificates and Declarations

Data Sheet, Technical Information	95MR7G-3.5
-----------------------------------	------------

### Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

### Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Airfield Lighting

