95MR7I-0.5 1/3



PRODUCT-DETAILS

## 95MR7I-0.5

## **CABLE ASBLY SCDRY FAA STL7**



General Information	
Extended Product Type	95MR7I-0.5
Product ID	7TBA136260R0545
Catalog Description	CABLE ASBLY SCDRY FAA STL7
Long Description	Cable Assembly Secondary FAA Style 7 Receptacle, 2/16 AWG (1.3mmsq) Thermoplastic Insulated Waterproof Cable with overall Jacket, Rated 600 Volts Between Contacts, 1500 Volts to Earth, 20 Amps, 90 Degrees Celsius, Outside Diameter 9.4mm (.37 inch), Length 0.5 meters.

Ordering	
UPC	708917328438
Country of Origin	United States (US)
Selling Unit of Measure	each

Container Information	
Package Level 1 Units	100 EA
Package Level 1 Width	25.4 mm

95MR7I-0.5 2/3

	1 in
Package Level 1 Height	25.4 mm
	1 in
Package Level 1 Depth /	25.4 mm
Length	1 in

Additional Information	
Brand / Label	Amerace
Current Rating	20 A
Effective Date	20091013
Insulation Material	Yes
Product Name	Other
Product Type	Secondary Cable Assembly - Receptacle FAA Style 7
Size	0.5 Meters Long
Standards	ISO 9001, ISO 14001, QMI/SAI Global Certified, CSA Listed, Teflon Wires Certified to UL1199 and CSA1 A/B
Voltage Rating	Between contacts 600 V To earth 1,500 V

Certificates and Declarations	
Data Sheet, Technical	95MR7I-0.5
Information	

Classifications	
UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

## **Categories**

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Cable\ Accessories\ and\ Apparatus \rightarrow Airfield\ Lighting$ 

95MR7I-0.5 3/3

