



SAFETY DATA SHEET PROPAN-2-OL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	PROPAN-2-OL
Product number	461
Synonyms; trade names	IPA,IPS,SEC PROPYL ALCOHOL,ISOPROPYL ALCOHOL,CAFSOL 2,EVERBLEND 15,AL11,IPA LOW ODOUR,ISOPROPANOL,ISOPROPANOL PC SSL,ISOPROPANOL PC SHL,ISOPROPANOL SSL,MX-THINNER HTS 83698,ISOPROPANOL SHELL,ISOPROPANOL EP,ISOPROPANOL (PHARMA),ISOPROPANOL MIN 99.5%,ISOPROPANOL MIN. 99.8%,ISOPROPANOL (IPA),ISOPROPANOL C+,ISOPROPYL ALCOHOL TT-I-735A,ISOPROPANOL PH SHL
REACH registration number	01-2119457558-25
CAS number	67-63-0
EU index number	603-117-00-0
EC number	200-661-7

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Industrial Solvent In household and cosmetic chemical industry. Pharmaceuticals Chemicals used in the synthesis and / or formulation of industrial products
------------------------	---

1.3. Details of the supplier of the safety data sheet

Supplier	Univar Aquarius House 6 Mid Point Business Park Bradford BD3 7AY +44 1274 267300 sds@univar.com +44 1274 267306
-----------------	--

1.4. Emergency telephone number

Emergency Contact Number (Outside Office Hours)	SGS - +32 (0)3 575 55 55 (24h)
Emergency Contact Number (Office Hours)	+44 1274 267346
Sds No.	461

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards	Flam. Liq. 2 - H225
Health hazards	Eye Irrit. 2 - H319 STOT SE 3 - H336

PROPAN-2-OL

Environmental hazards Not Classified

Classification (67/548/EEC or 1999/45/EC) F; R11. Xi; R36. R67

2.2. Label elements

EC number 200-661-7

Pictogram



Signal word Danger

Hazard statements
 H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Precautionary statements
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P261 Avoid breathing vapour/spray.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P501 Dispose of contents/container in accordance with national regulations.

2.3. Other hazards

None.

SECTION 3: Composition/information on ingredients

3.1. Substances

Product name PROPAN-2-OL
REACH registration number 01-2119457558-25
EU index number 603-117-00-0
CAS number 67-63-0
EC number 200-661-7

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Move affected person to fresh air at once. Get medical attention.

Ingestion Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Rinse mouth thoroughly with water. Give plenty of water to drink. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

PROPAN-2-OL

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Vapours may irritate throat/respiratory system. Symptoms following overexposure may include the following: Coughing. May cause drowsiness or dizziness.
Ingestion	Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
Skin contact	Product has a defatting effect on skin. Dryness and/or cracking.
Eye contact	Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Oxides of the following substances: Carbon. The product is highly flammable. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.
-------------------------	---

5.3. Advice for firefighters

Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Follow precautions for safe handling described in this safety data sheet. Take precautionary measures against static discharges. Provide adequate ventilation.
-----------------------------	--

6.2. Environmental precautions

Environmental precautions	Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.
----------------------------------	---

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with inert, damp, non-combustible material. Flush contaminated area with plenty of water. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.
--------------------------------	--

6.4. Reference to other sections

Reference to other sections	For personal protection, see Section 8. For waste disposal, see section 13.
------------------------------------	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions	Avoid spilling. Keep away from heat, sparks and open flame. Storage tanks and other containers must be earthed. Avoid contact with skin and eyes. Use mechanical ventilation in case of handling which causes formation of vapours.
--------------------------	---

PROPAN-2-OL

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions	Keep away from heat, sparks and open flame. Store in tightly-closed, original container in a well-ventilated place.
Storage class	Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s)	The identified uses for this product are detailed in Section 1.2.
----------------------------	---

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³

WEL = Workplace Exposure Limit

DNEL	Industry - Dermal; Long term systemic effects: 888 mg/kg/day Industry - Inhalation; Long term systemic effects: 500 mg/m ³ Consumer - Dermal; Long term systemic effects: 319 mg/kg/day Consumer - Inhalation; Long term systemic effects: 89 mg/m ³ Consumer - Oral; Long term systemic effects: 26 mg/kg/day
-------------	--

PNEC	- Fresh water; 140.9 mg/l - Marine water; 140.9 mg/l - Intermittent release; 140.9 mg/l - STP; 2251 mg/l - Sediment (Freshwater); 552 mg/kg - Sediment (Marinewater); 552 mg/kg - Soil; 28 mg/kg
-------------	--

8.2. Exposure controls

Protective equipment



Eye/face protection	The following protection should be worn: Chemical splash goggles. EN 166
Hand protection	Use protective gloves. Nitrile rubber. EN 374
Other skin and body protection	Wear apron or protective clothing in case of contact.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn. EN 136/140/145/143/149

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Colourless.
Odour	Alcoholic.
pH	Data lacking.

PROPAN-2-OL

Melting point	-88°C
Initial boiling point and range	82 - 83°C @
Flash point	12°C
Evaporation rate	1.5
Upper/lower flammability or explosive limits	Upper flammable/explosive limit: 12 Lower flammable/explosive limit: 2.0
Vapour pressure	6020 Pa @ °C
Vapour density	2
Relative density	0.78-0.79 @ @ 20°C
Bulk density	Data lacking. «59» «184» «109012»
Solubility(ies)	Soluble in water.
Partition coefficient	log Pow: 0.05
Auto-ignition temperature	425°C
Decomposition Temperature	Data lacking.
Viscosity	2.43 mPa s @ 20°C
Explosive properties	Data lacking.
Oxidising properties	Not available.
9.2. Other information	
Refractive index	1.377 at 20C
Molecular weight	60.1

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity The following materials may react with the product: Strong oxidising agents. Strong acids.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Solvent vapours may form explosive mixtures with air.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Strong acids. Alkali metals. Amines. Aluminium. Iron.

10.6. Hazardous decomposition products

Hazardous decomposition products Oxides of the following substances: Carbon.

SECTION 11: Toxicological information

PROPAN-2-OL

11.1. Information on toxicological effects

Acute toxicity - oral

Acute toxicity oral (LD₅₀
mg/kg) 5,000.0

Species Rat

Notes (oral LD₅₀) LD₅₀ >5000 mg/kg, Oral, Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀
mg/kg) 5,000.0

Species Rabbit

Notes (dermal LD₅₀) LD₅₀ >5000 mg/kg, Dermal, Rabbit

Skin corrosion/irritation

Animal data Not irritating.

Respiratory sensitisation

Respiratory sensitisation Not sensitising.

Skin sensitisation

Skin sensitisation Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vivo Data lacking.

Carcinogenicity

Carcinogenicity There is no evidence that the product can cause cancer.

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

Reproductive toxicity

Reproductive toxicity - fertility Data lacking.

Specific target organ toxicity - single exposure

STOT - single exposure Data lacking.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Data lacking.

Inhalation May cause respiratory system irritation. Vapours may cause drowsiness and dizziness.

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Skin contact Prolonged contact may cause dryness of the skin.

Eye contact Irritating to eyes.

SECTION 12: Ecological Information

Ecotoxicity The product is not expected to be toxic to aquatic organisms.

12.1. Toxicity

Toxicity Not considered toxic to fish.

PROPAN-2-OL

Acute toxicity - fish LC₅₀, 48 hours: >100 mg/l, Leuciscus idus (Golden orfe)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: >100 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: >100 mg/l, Scenedesmus subspicatus

12.2. Persistence and degradability

Persistence and degradability The substance is readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product is not bioaccumulating.

Partition coefficient log Pow: 0.05

12.4. Mobility in soil

Mobility The product is soluble in water.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Do not puncture or incinerate, even when empty. Materials such as cleaning rags and paper wipes that are contaminated with flammable liquids may self-ignite after use and should be stored in designated fireproof containers with tight-fitting, self-closing lids.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1219

UN No. (IMDG) 1219

UN No. (ICAO) 1219

14.2. UN proper shipping name

Proper shipping name (ADR/RID) ISOPROPANOL (ISOPROPYL ALCOHOL)

Proper shipping name (IMDG) ISOPROPANOL (ISOPROPYL ALCOHOL)

Proper shipping name (ICAO) ISOPROPANOL (ISOPROPYL ALCOHOL)

Proper shipping name (ADN) ISOPROPANOL (ISOPROPYL ALCOHOL)

14.3. Transport hazard class(es)

ADR/RID class 3

PROPAN-2-OL

ADR/RID subsidiary risk

ADR/RID label 3

IMDG class 3

IMDG subsidiary risk

ICAO class/division 3

ICAO subsidiary risk

Transport labels



14.4. Packing group

ADR/RID packing group II

IMDG packing group II

ICAO packing group II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-E, S-D

Emergency Action Code •2YE

Hazard Identification Number (ADR/RID) 33

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Cat Z

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
This product may impact SEVESO storage regulations.

Water hazard classification WGK 1

15.2. Chemical safety assessment

PROPAN-2-OL

A chemical safety assessment has been carried out.

Inventories

EU - EINECS/ELINCS

All the ingredients are listed or exempt.

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

Australia - AICS

All the ingredients are listed or exempt.

Philippines – PICCS

All the ingredients are listed or exempt.

SECTION 16: Other information

Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	22/10/2015
Revision	04
SDS number	461
SDS status	Approved.
Signature	Jitendra Panchal
Risk phrases in full	R11 Highly flammable. R36 Irritating to eyes. R67 Vapours may cause drowsiness and dizziness.
Hazard statements in full	H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.