

PRODUCT-DETAILS

# 442352S

## XTE350S-230/LTC



### General Information

Extended Product Type	442352S
Product ID	7TCA304020R0004
EAN	5415022526813
Catalog Description	XTE350S-230/LTC
Long Description	Luminaire for central battery - Optima Waterproof 230/1000L - LTC

### Technical

Function	Escape route lighting/signage
Rated Voltage ( $U_r$ )	230 V
Input Voltage Type	AC
	10.5 W
Power Supply Type	Central (Central Battery)
Number of Poles	2
Number of Lamps	40
Number of Lighting Heads	0
Functional Testing Capability	Safety Module for Monitoring (Central Fedded System)
Wiring Configuration	Standby switching Suitable for through wiring
Ballast Type	LED Operating Device Current Controlled

Connection Type	Screw
Lamp Type	LED not exchangeable
Light Distribution Type	Reflector
Marking Type	Plate
Mounting Type	Wall surface mounted / ceiling surface mounting
Type of Indicator	Single-sided
Cover Material	Plastic, Opal
Housing Material	Plastic
Communication	EMEX test
Illuminance	950 lm
Housing Color	White
Number of Batteries	0
	6000 K

## Environmental

Ambient Temperature	IEC62722-2-1 0...40 °C
Degree of Protection	IP65
Protection Class	Isolated (Class II)

## Dimensions

Product Net Width	66 mm
Product Net Height	116 mm
Product Net Depth / Length	237 mm
Built-In Depth (t <sub>2</sub> )	66 mm

## Ordering

Minimum Order Quantity	1 piece
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	605 g
UPC	075114434591

## Installation

Instructions and Manuals	442352S
--------------------------	---------

## Popular Downloads

Data Sheet, Technical Information	442352S
-----------------------------------	---------

## Classifications

ETIM 8	EC001957 - Emergency luminaire
ETIM 9	EC001957 - Emergency luminaire
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---

## Categories

---

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Emergency Lighting

