

TECHNICAL DATA SHEET - INTERACTIVE PDF

Plugs, knockout hole plugs

Accessories for enclosures

T&B Liquidtight Systems[®]



Knockout hole plugs provide a water, dust and oil tight seal for unused knockouts.

Certifications / Standards:



3-Part Specification:

End User Tools

Features:

- No tools are required to install. Push the plug into the knockout hole, and it will snap in.
- Not necessary to replace NEMA 1, 4, 4X, 12 or 13 boxes when a knockout is no longer used.
- Available in ½" to 4" trade sizes.

Applications:

- Provides a water, dust and oil tight seal for unused NPT knockout hole sizes.
- Not suitable for use with Metric or PG hole sizes.
- Efficient and effective installation process.

Material / Finishes:

- Neoprene, flame retardant

Working Temperature:

- Range: -30 to +105°C (-22 to +221°F)

Conforms to:

- UL514B, Conduit, Tubing and Cable Fittings:
 - File: E13938
- UL 50E & CSA22.2 No. 94.2-15, Enclosures for Electrical Equipment, Environmental Considerations:
 - File: E506371
- UL 508A, Industrial Control Panels:
 - File: E506371

UL & NEMA System Ingress Ratings:


- UL Listed type ratings tested to UL 50E requirements
- UL File No: E13938
 - Type 1, 4, 4X, 12, 13
- NEMA
 - Type 1, 4, 4X, 12, 13

IEC System Ingress Ratings:

- IEC Ingress Ratings:
 - IP66, IP67

NPT knockout hole plug sizes:

Product selection		
Part nos.	Hole size (inch)	A (inch)
5710	½	1 ⁹ / ₃₂
5711-TB	¾	1½
5712	1	1 ²⁷ / ₃₂
5713	1¼	2 ⁷ / ₃₂
5714-TB	1½	2½
5715	2	3 ³ / ₃₂
5716	2½	3 ²¹ / ₃₂
5717-TB	3	4 ¹⁹ / ₆₄
5718	4	5 ¹⁹ / ₆₄



Note: Product must be installed in accordance with applicable national and local electrical codes.