

PRODUCT SPECIFICATION

XT100E

PrimEvo Self-Contained 20M IP65 Surface/Wall

Catalogue Number **XT100E**
GID **7TCA091160R0499**
Warranty **3 Year/s Refer to ABB warranty terms & conditions**
Power Supply System **Self-Contained (individual battery)**
Mounting Method/Form **Ceiling, Wall Surface, Recessed**
Housing Material **Polycarbonate**
Colour **White**
Dimensions (LxWxD) **240 x 115 x 78 mm**
Temperature Range **0 to 40°C**
Weight **0.4 Kg**

Emergency Duration (Hours) **3 Hours**
Battery **tbc**
Monitoring Equipment **None**
Lamp **2 x 0.5W LED**
Emergency Light Output (Lumens) **110**
Average Lifespan light source (Hours) **Hours**
Light Colour/Temperature/CRI **White / / 70**
Degree of Protection **IP65 IK10**

Type of Legend **Single Sided**
Exit Sign Viewing/Recognition Distance (m) **20**
Nominal Voltage **220-240v AC 50/60Hz**
Power Consumption **5 VA / 2 Watts**
Current **Nominal: 21.7mA (mA)**

Accessories

- 642 015** Protective Grid Cover
- 642 102** Recess Kit 50%
- 642 202** Recess Kit 100%
- 663 325** Pictogram Holder (inc. 3 Legends)
- 663 330** Pack of 3 Legends



Bulkhead

Configurable pictograms included

