

TECHNICAL DATA SHEET

Terminals, receptacle disconnects

Vinyl-insulated, double crimp

Spec-Kon®



Vinyl-insulated receptacle disconnects for wire termination of copper conductors ranging from 0.5mm² to 6mm²

Certifications / Standards:



Features:

- Easy entry double crimp
- Corrosive resistant plating
- Color coded to wire size range

Maximum rating:

- 75°C Max
- 600 volts
- Copper conductors only

Application tool:

- ERG9003

Conforms to:

- IEC 60352-2

Materials / Finishes:

- Brass disconnect
- Electro-Tin plated
- Vinyl insulation

Product selection

Drawing	Part no:	Wire size range (mm ²)	Color	Dimensions (mm)				Crimping tool
				L	F	W	D	
	RD1.5-39VDC	0.5-1.5	Red	19.8	7.3	3.9	3.3	ERG9003
	RD2.5-39VDC	1.5-2.5	Blue	19.8	7.3	3.9	4.1	
	RD2.5-49VDC	1.5-2.5	Blue	21.5	8.5	4.9	4.1	
	RD6-49VDC	4.0-6.0	Yellow	24.5	8.5	4.9	5.6	

Note: Products must be installed in accordance with applicable national and local electrical codes.