



# High Efficiency Thyristor

Single Thyristor

$V_{RRM} = 1200 \text{ V}$   
 $I_{T(AV)M} = 30 \text{ A}$   
 $I_{T(RMS)} = 47 \text{ A}$

Part number

CLA 30 E 1200 PB



Backside: anode

## Features / Advantages:

- Thyristor for line frequency
- Planar passivated chip
- Long-term stability

## Applications:

- Softstart AC motor control
- DC Motor control
- Power converter
- AC power control
- Lighting and temperature control


## Package:

- Housing: TO-220
- Industry standard outline
- Epoxy meets UL 94V-0
- RoHS compliant

Symbol	Definition	Conditions	Ratings			
			min.	typ.	max.	Unit
$V_{RSM/DSM}$	max. non-repetitive reverse/forward blocking voltage	$T_{VJ} = 25^\circ\text{C}$			1300	V
$V_{RRM/DRM}$	max. repetitive reverse/forward blocking voltage	$T_{VJ} = 25^\circ\text{C}$			1200	V
$I_{R/D}$	reverse current, drain current	$V_{R/D} = 1200 \text{ V}$	$T_{VJ} = 25^\circ\text{C}$		10	$\mu\text{A}$
		$V_{R/D} = 1200 \text{ V}$	$T_{VJ} = 125^\circ\text{C}$		2	mA
$V_T$	forward voltage drop	$I_T = 30 \text{ A}$	$T_{VJ} = 25^\circ\text{C}$		1.30	V
		$I_T = 60 \text{ A}$			1.59	V
		$I_T = 30 \text{ A}$	$T_{VJ} = 125^\circ\text{C}$		1.27	V
		$I_T = 60 \text{ A}$			1.65	V
$I_{T(AV)M}$	average forward current	$T_C = 115^\circ\text{C}$	$T_{VJ} = 150^\circ\text{C}$		30	A
$I_{T(RMS)}$	RMS forward current	180° sine			47	A
$V_{TO}$ $r_T$	threshold voltage slope resistance } for power loss calculation only		$T_{VJ} = 150^\circ\text{C}$		0.86	V
					13.2	$\text{m}\Omega$
$R_{thJC}$	thermal resistance junction to case				0.65	K/W
$T_{VJ}$	virtual junction temperature		-40		150	$^\circ\text{C}$
$P_{tot}$	total power dissipation	$T_C = 25^\circ\text{C}$			190	W
$P_{GM}$	max. gate power dissipation	$t_p = 30 \mu\text{s}$	$T_C = 150^\circ\text{C}$		10	W
		$t_p = 300 \mu\text{s}$			5	W
$P_{GAV}$	average gate power dissipation				0.5	W
$I_{TSM}$	max. forward surge current	$t = 10 \text{ ms}; (50 \text{ Hz}), \text{sine}$	$T_{VJ} = 45^\circ\text{C}$		300	A
		$t = 8,3 \text{ ms}; (60 \text{ Hz}), \text{sine}$	$V_R = 0 \text{ V}$		325	A
		$t = 10 \text{ ms}; (50 \text{ Hz}), \text{sine}$	$T_{VJ} = 150^\circ\text{C}$		255	A
		$t = 8,3 \text{ ms}; (60 \text{ Hz}), \text{sine}$	$V_R = 0 \text{ V}$		275	A
$I^2t$	value for fusing	$t = 10 \text{ ms}; (50 \text{ Hz}), \text{sine}$	$T_{VJ} = 45^\circ\text{C}$		450	$\text{A}^2\text{s}$
		$t = 8,3 \text{ ms}; (60 \text{ Hz}), \text{sine}$	$V_R = 0 \text{ V}$		440	$\text{A}^2\text{s}$
		$t = 10 \text{ ms}; (50 \text{ Hz}), \text{sine}$	$T_{VJ} = 150^\circ\text{C}$		325	$\text{A}^2\text{s}$
		$t = 8,3 \text{ ms}; (60 \text{ Hz}), \text{sine}$	$V_R = 0 \text{ V}$		315	$\text{A}^2\text{s}$
$C_J$	junction capacitance	$V_R = 400 \text{ V} \quad f = 1 \text{ MHz}$	$T_{VJ} = 25^\circ\text{C}$	13		pF

Ratings					
Symbol	Definition	Conditions	min.	typ.	max.
$(di/dt)_{cr}$	critical rate of rise of current	$T_{VJ} = 150^\circ C$ repetitive, $I_T = 40 A$ $f = 50 \text{ Hz}; t_p = 200 \mu s$ $I = 0.3 A; di/dt = 0.3 A/\mu s$ $V_D = \frac{2}{3} V_{DRM}$ non-repetitive, $I_T = 30 A$			150 A/ $\mu s$
$(dv/dt)_{cr}$	critical rate of rise of voltage	$V_D = \frac{2}{3} V_{DRM}$ $T_{VJ} = 150^\circ C$ $R_{GK} = \infty$ ; method 1 (linear voltage rise)			500 V/ $\mu s$
$V_{GT}$	gate trigger voltage	$V_D = 6 V$ $T_{VJ} = 25^\circ C$ $T_{VJ} = -40^\circ C$			1.3 V
$I_{GT}$	gate trigger current	$V_D = 6 V$ $T_{VJ} = 25^\circ C$ $T_{VJ} = -40^\circ C$			30 mA
$V_{GD}$	gate non-trigger voltage	$V_D = \frac{2}{3} V_{DRM}$ $T_{VJ} = 150^\circ C$			0.2 V
$I_{GD}$	gate non-trigger current				1 mA
$I_L$	latching current	$t_p = 10 \mu s$ $T_{VJ} = 25^\circ C$ $I = 0.3 A; di/dt = 0.3 A/\mu s$			90 mA
$I_H$	holding current	$V_D = 6 V$ $R_{GK} = \infty$ $T_{VJ} = 25^\circ C$			60 mA
$t_{gd}$	gate controlled delay time	$V_D = \frac{1}{2} V_{DRM}$ $T_{VJ} = 25^\circ C$ $I = 0.3 A; di/dt = 0.3 A/\mu s$			2 $\mu s$
$t_q$	turn-off time	$V_R = 100 V; I_T = 30 A$ $T_{VJ} = 150^\circ C$ $V_D = \frac{2}{3} V_{DRM}; t_p = 200 \mu s$ $di/dt = 10 A/\mu s; dv/dt = 20 V/\mu s$		150	$\mu s$

Symbol	Definition	Conditions	Ratings		
			min.	typ.	max.
$I_{RMS}$	RMS current	per terminal		35	A
$R_{thCH}$	thermal resistance case to heatsink			0.50	K/W
$T_{stg}$	storage temperature		-55		150
<b>Weight</b>				2	g
$M_D$	mounting torque		0.4		0.6 Nm
$F_c$	mounting force with clip		20		60 N


**Part number****Product Marking**

C = Thyristor (SCR)  
 L = High Efficiency Thyristor  
 A = (up to 1200 V)  
 30 = Current Rating [A]  
 E = Single Part  
 1200 = Reverse Voltage [V]  
 PB = TO-220AB (3)

Ordering	Part Name	Marking on Product	Delivering Mode	Base Qty	Code Key
Standard	CLA 30 E 1200 PB	CLA30E1200PB	Tube	50	508228

Similar Part	Package	Voltage class
CLA30E1200HB	TO-247AD (3)	1200
CLA30E1200PC	TO-263AB (D2Pak)	1200
CS22-12io1M	TO-220ABFP (3)	1200
CS22-08io1M	TO-220ABFP (3)	800
CMA30E1600PN	TO-220ABFP (3)	1600
CMA30E1600PB	TO-220AB (3)	1600

## Outlines TO-220



Dim.	Millimeter		Inches	
	Min.	Max.	Min.	Max.
A	4.32	4.82	0.170	0.190
A1	1.14	1.39	0.045	0.055
A2	2.29	2.79	0.090	0.110
b	0.64	1.01	0.025	0.040
b2	1.15	1.65	0.045	0.065
C	0.35	0.56	0.014	0.022
D	14.73	16.00	0.580	0.630
E	9.91	10.66	0.390	0.420
e	2.54	BSC	0.100	BSC
H1	5.85	6.85	0.230	0.270
L	12.70	13.97	0.500	0.550
L1	2.79	5.84	0.110	0.230
ØP	3.54	4.08	0.139	0.161
Q	2.54	3.18	0.100	0.125




Fig. 1 Forward characteristics







Fig. 2 Surge overload current  
 $I_{TSM}$ : crest value,  $t$ : durationFig. 3  $I^2t$  versus time (1-10 s)Fig. 4 Gate voltage & gate current  
Triggering: A = no; B = possible; C = safeFig. 5 Gate controlled delay time  $t_{gd}$ Fig. 6 Max. forward current at  
case temperature

Fig. 7 Transient thermal impedance junction to case

Constants for  $Z_{thJC}$  calculation:

i	$R_{thi}$ (K/W)	$t_i$ (s)
1	0.024	0.0007
2	0.069	0.0018
3	0.148	0.018
4	0.053	0.12
5	0.356	0.76