



Powerex, Inc., 200 Hillis Street, Youngwood, Pennsylvania 15697-1800 (412) 925-7272
 Powerex, Europe, S.A. 428 Avenue G. Durand, BP107, 72003 Le Mans, France (43) 41.14.14

Phase Control SCR

1200 Amperes Average
 2400 Volts



T9G0 1200A Phase Control SCR
 1200 Amperes Average, 2400 Volts

T9G0 1200A (Outline Drawing)

Description:

Powerex Silicon Controlled Rectifiers (SCR) are designed for phase control applications. These are all-diffused, Press-Pak, hermetic Pow-R-Disc devices employing the field proven amplifying gate.

Features:

- Low On-State Voltage
- High di/dt Capability
- High dv/dt Capability
- Hermetic Packaging
- Excellent Surge and I^2t Ratings

Applications:

- Power Supplies
- Motor Control

Ordering Information:

Select the complete 12 digit part number you desire from the table below.

| Type | Voltage | Current | Turn-off | Gate Current | Lead Code |
|------|---|--------------------|----------------------------------|------------------|---------------|
| | V_{DRM}/V_{RRM} (Volts) | $I_{T(av)}$ (A) | t_q (μ sec) | I_{GT} (mA) | |
| T9G0 | 02 through 24 200V through 2400V | 12 1200A | 0 350 μ sec (Typical) | 3 200mA | DH 12" |



Powerex, Inc., 200 Hillis Street, Youngwood, Pennsylvania 15697-1800 (412) 925-7272
Powerex, Europe, S.A. 428 Avenue G. Durand, BP107, 72003 Le Mans, France (43) 41.14.14

T9G0 1200A
Phase Control SCR
1200 Amperes Average, 2400 Volts

Absolute Maximum Ratings

| Characteristics | Symbol | T9G0 1200A | Units |
|---|-------------|------------------|--------------------|
| Non-repetitive Transient Peak Reverse Voltage | V_{RSM} | $V_{RRM} + 100V$ | Volts |
| RMS On-state Current, $T_C = 85^\circ C$ | $I_T(rms)$ | 1880 | Amperes |
| Average Current 180° Sine Wave, $T_C = 85^\circ C$ | $I_T(av)$ | 1200 | Amperes |
| RMS On-state Current, $T_C = 55^\circ C$ | $I_T(rms)$ | 2790 | Amperes |
| Average Current 180° Sine Wave, $T_C = 55^\circ C$ | $I_T(av)$ | 1780 | Amperes |
| Peak One Cycle Surge On-state Current (Non-repetitive) 60Hz | I_{tsm} | 27000 | Amperes |
| Peak One Cycle Surge On-state Current (Non-repetitive) 50Hz | I_{tsm} | 24650 | Amperes |
| Critical Rate-of-rise of On-state Current (Non-repetitive) | di/dt | 300 | A/ μ sec |
| Critical Rate-of-rise of On-state Current (Repetitive) | di/dt | 150 | A/ μ sec |
| I^2t (for Fusing) for One Cycle, 60Hz | I^2t | 3,040,000 | A ² sec |
| Peak Gate Power Dissipation | P_{GM} | 16 | Watts |
| Average Gate Power Dissipation | $P_{G(av)}$ | 3 | Watts |
| Operating Temperature | T_j | -40 to +125°C | °C |
| Storage Temperature | T_{stg} | -40 to +150°C | °C |
| Approximate Weight | | 1 | lb. |
| | | 454 | g |
| Mounting Force | | 5000 to 5500 | lb. |
| | | 2270 to 2500 | kg. |



Powerex, Inc., 200 Hillis Street, Youngwood, Pennsylvania 15697-1800 (412) 925-7272
 Powerex, Europe, S.A. 428 Avenue G. Durand, BP107, 72003 Le Mans, France (43) 41.14.14

T9G0 1200A
Phase Control SCR
 1200 Amperes Average, 2400 Volts

Electrical Characteristics, $T_j = 25^\circ\text{C}$ Unless Otherwise Specified

| Characteristics | Symbol | Test Conditions | Min. | Typ. | Max. | Units |
|---|-------------|--|------|------|---------|--|
| Repetitive Peak Reverse Leakage Current | I_{RRM} | $T_j = 125^\circ\text{C}, V_R = V_{RRM}$ | | | 75 | mA |
| Repetitive Peak Forward Leakage Current | I_{DRM} | $T_j = 125^\circ\text{C}, V_D = V_{DRM}$ | | | 75 | mA |
| Peak On-state Voltage | V_{TM} | $I_{TM} = 1500\text{A Peak}$ Duty Cycle < 0.1% | | | 1.35 | Volts |
| Threshold Voltage, Low-level | $V_{(TO)1}$ | $T_j = 125^\circ\text{C}, I = 15\%, I_{T(av)}$ to $\pi I_{T(av)}$ | | | 0.60559 | Volts |
| Slope Resistance, Low-level | r_{T1} | | | | 0.2681 | m Ω |
| Threshold Voltage, High-level | $V_{(TO)2}$ | $T_j = 125^\circ\text{C}, I = \pi I_{T(av)}$ to I_{TSM} | | | 0.64284 | Volts |
| Slope Resistance, High-level | r_{T2} | | | | 0.1906 | m Ω |
| V_{TM} Coefficients, Low-level | | $T_j = 125^\circ\text{C}, I = 15\% I_{T(av)}$ to $\pi I_{T(av)}$ | | | | $A_1 = -0.55126$ $B_1 = 0.21303$ $C_1 = 1.433\text{E-}04$ $D_1 = -0.003097$ |
| V_{TM} Coefficients, High-level | | $T_j = 125^\circ\text{C}, I = \pi I_{T(av)}$ to I_{TSM} | | | | $A_1 = -62.5287$ $B_1 = 10.457$ $C_1 = 0.001238$ $D_1 = -0.43650$ |
| Typical Turn-on Time | t_{on} | $I_{TM} = 1000\text{A}, V_D = 450\text{V}$ | | 3 | | μsec |
| Typical Turn-off Time | t_q | $T_j = 125^\circ\text{C}, I_T = 250\text{A},$ $di_R/dt = 50\text{A}/\mu\text{sec}$ Reapplied $dv/dt = 20\text{V}/\mu\text{sec}$ Linear to 80% V_{DRM} | | 350 | | μsec |
| Minimum Critical dv/dt - Exponential to $V_{DRN=M}$ | dv/dt | $T_j = 125^\circ\text{C}$ | 300 | | | V/ μsec |
| Gate Trigger Current | I_{GT} | $T_j = 25^\circ\text{C}, V_D = 12\text{V}$ | | | 200 | mA |
| Gate Trigger Voltage | V_{GT} | $T_j = 25^\circ\text{C}, V_D = 12\text{V}$ | | | 3.0 | Volts |
| Non-Trigging Gate Voltage | V_{GDM} | $T_j = 125^\circ\text{C}, V_D = V_{DRM}$ | | | 0.15 | Volts |
| Peak Forward Gate Current | I_{GTM} | | | | 4 | A |
| Peak Reverse Gate Voltage | V_{GRM} | | | | 5 | Volts |

Thermal Characteristics


Maximum Thermal Resistance, Double Sided Cooling

| | | | | |
|------------------|-------------------|--|--------|---------------------------|
| Junction-to-Case | $R_{\theta(j-c)}$ | | 0.023 | $^\circ\text{C}/\text{W}$ |
| Case-to-Sink | $R_{\theta(c-s)}$ | | 0.0075 | $^\circ\text{C}/\text{W}$ |


Powerex, Inc., 200 Hillis Street, Youngwood, Pennsylvania 15697-1800 (412) 925-7272
 Powerex, Europe, S.A. 428 Avenue G. Durand, BP107, 72003 Le Mans, France (43) 41.14.14

T9G0 1200A
Phase Control SCR
 1200 Amperes Average, 2400 Volts


Maximum On-State Forward Voltage Drop
 ($T_J = 125^\circ\text{C}$)




Maximum Transient Thermal Impedance
 (Junction to Case)




Maximum On-State Power Dissipation
 (Sinusoidal Waveform)



Maximum Allowable Case Temperature
 (Sinusoidal Waveform)



Maximum On-State Power Dissipation
 (Rectangular Waveform)



Maximum Allowable Case Temperature
 (Rectangular Waveform)

