


Belt driven linear actuator ELGR-TB-...-45- -

Part number: 560506

FESTO



Data sheet

Feature	Value
Drive pinion effective diameter	24.83 mm
Working stroke	50 mm...1000 mm
Size	45
Toothed belt elongation	0.08 %
Toothed belt pitch	3 mm
Mounting position	Any
Guide	Sliding guide Recirculating ball bearing guide
Structural design	Electromechanical linear axis with toothed belt
Motor type	Stepper motor Servo motor
Max. acceleration	50 m/s ²
Max. speed	1 m/s...3 m/s
Repetition accuracy	±0.1 mm
Duty cycle	100%
LABS (PWIS) conformity	VDMA24364 zone III
Degree of protection	IP20
Ambient temperature	-10 °C...50 °C
2nd moment of area I _y	15700 mm ⁴
2nd moment of area I _z	17940 mm ⁴
Max. driving torque	1.24 Nm
Max. force F _y	100 N
Max. force F _z	100 N
Max. no-load resistance to shifting	16.1 N
Max. feed force F _x	100 N
No-load driving torque	0.2 Nm
Mass moment of inertia J _H per meter of stroke	0.11 kgcm ²
Mass moment of inertia J _L per kg of payload	1.54 kgcm ²
Feed constant	78 mm/U
Reference service life	5000 km
Additional moving mass per 10 mm stroke	0.69 g

Feature	Value
Basic weight with 0 mm stroke	3230 g
Additional weight per 10 mm stroke	50 g
Profile material	Wrought aluminum alloy Anodized
Note on materials	RoHS-compliant
Drive cover material	Wrought aluminum alloy Anodized
Belt pulley material	High-alloy stainless steel
Slide material	Wrought aluminum alloy Anodized
Toothed belt clamping component material	Beryllium bronze
Toothed belt material	Polychloroprene with glass cord and nylon coating