

# Manifold sub-base VABX-A-P-EL-E12-MF1-SHUH

Part number: 8188451

FESTO



## Data sheet

Feature	Value
Max. no. of solenoid coils	24
Dimensions W x L x H	45 mm x 104.3 mm x 53.3 mm
Note regarding operating voltage	SELV/PELV fixed power supplies required Note voltage drop
Certification	RCM compliance mark
KC characters	KC EMC
CE marking (see declaration of conformity)	As per EU EMC directive As per EU RoHS directive
UKCA marking (see declaration of conformity)	To UK instructions for EMC To UK RoHS instructions
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Storage temperature	-20 °C...70 °C
Relative air humidity	5 - 95 %
Degree of protection	IP40
Ambient temperature	-5 °C...50 °C
Max. tightening torque for wall mounting	6 Nm
Product weight	124.1 g
Electrical connection 1, connection technology	Sub-D
Cable outlet	Straight
Sub-base mounting type	With through-hole
Pneumatic connection 1	For 15 mm cartridge
Pneumatic connection 5	For 15 mm cartridge
Note on materials	RoHS-compliant
Material of sub-base	PA-reinforced
Cover material	PA-reinforced
Seals material	NBR
Sleeve material	High-alloy stainless steel
Clip material	High-alloy stainless steel
Nut material	High-alloy stainless steel