


**Note:**  
 - Drawings Not To Scale  
 - Drawings Subject to Change Without Notice  
 - Dimensions are inches next to [Millimeters]

Part No.:

**LP4K09107SW3**



Schneider Electric United States  
 North American Division  
 Boston One Campus  
 800 Federal Street  
 Andover, MA 01810, USA  
 Phone: +1 8773425173  
 Email: CCC@us.schneider-electric.com

**Technical Information:**

Rating: 600V / 9A  
 UL File/CCN: E164353 / NKCR  
 CSA File: LR43364 3211 03  
 Meets Standards: IEC 60647-1-1  
 Weight: 0.52 lb (0.19 kg)  
 Termination Method: Slip-on Terminal  
 Wire Size: Power: 2 x 0.11 in or 1 x 0.25 in (2 x 2.80mm or 1 x 6.35mm)  
 Control: 2 x 0.11 in or 1 x 0.25 in (2 x 2.80mm or 1 x 6.35mm)  
 Terminal torque: Power: N/A  
 Control: N/A  
 Mounting Hwd.: 35mm DIN Rail, 4mm screw

**Specification:**

Description: TeSys K Non-reversing Contactor  
 Type: TeSys K IEC Contactor - 9A - 60Vdc Coil  
 Voltages Code: SW3 at 72Vdc

Coil Consumption: Inrush 1.8 W  
 Sealed 1.8 W

| Single Phase |        | Three Phase |      |      |      |
|--------------|--------|-------------|------|------|------|
| 115V         | 230V   | 200V        | 230V | 460V | 575V |
| 0.5 HP       | 1.5 HP | 2 HP        | 3 HP | 5 HP | 5 HP |