

APC Service Bypass Panel

Service Bypass Panels with a BBM switch for use with APC Smart-UPS® products up to 3kVA.

SBP1500RM



Designed to work with the world's most popular network and server UPS.

SBP2200RM



The Service Bypass Panels provide a wrap around system to allow easy maintenance of a UPS by isolating it from the critical load. The panels can be rack (2U) or wall mounted and are available with an integrated Power Distribution Unit (PDU).


- *Reliable*
- *Compact*
- *Easy to use*
- *Break Before Make (BBM) switch*

SBP3000RM



APC Service Bypass Panel

SBP1500RM



Standard features:

1 Bypass/UPS switch allows the switching of the supply to the load between the incoming supply and the UPS, so the UPS can be isolated for maintenance.

2 Equipment Outlets allowing the SBP to support multiple loads.

3 Output receptacle to feed UPS input.

4 Input receptacle to receive the output from the UPS.

5 Input receptacle to receive the external supply (utility).

SBP2200RM



6 Equipment outlet circuit breaker providing outlet protection.

SBP3000RM



Product feature	SBP1500RM	SBP2200RM	SBP3000RM
Input / Output ratings			
Nominal Input/Output voltage	120V	120V	120V
Maximum total current	15A	20A	16A
Switch characteristics			
Type / Transfer Time	Break Before Make (BBM) / 4ms max.		
Connections			
External supply input connection	NEMA 5-15P	NEMA 5-20P	NEMA L5-30P
UPS Input / Output connections	NEMA 5-15P	NEMA 5-20P	NEMA L5-30P
Load connections	NEMA 5-15R (8)	NEMA 5-15R (6) NEMA 5-20R (2)	NEMA 5-20R (4) NEMA L5-30R (1)
Physical			
Dimensions (H x W x D)	3.5" x 17.0" x 3.0" (89.00mm x 432.00mm x 76.00mm)		
Net weight	6.5 lbs (2.95 kg)	6.5 lbs (2.95 kg)	9.8 lbs (4.45 kg)
Conformance			
Regulatory Approvals	TUV		
Standard Warranty	2 years repair or replace		
Environmental Compliance	RoHS 7b Exemption, REACH: Contains No SVHCs		