



**Note:**  
 - Drawings Not To Scale  
 - Drawings Subject to Change Without Notice  
 - Dimensions are inches next to [Millimeters]

Part No.:  
**T36GN13L7**

**Schneider Electric**  
 Schneider Electric United States  
 North American Division  
 Boston One Campus  
 800 Federal Street  
 Andover, MA 01810, USA  
 Phone: +1 8773425173  
 Email: CCC@us.schneider-electric.com

**Technical Information:**  
 Max. Continuous Current Rating: 600V / 270A  
 Certifications: UL Listed, CSA, CE  
 RoHS: Yes  
 Termination Method: Power Line: Screw Clamp, Power Load: Lug, Control Circuit: Screw Clamp  
 Weight (lbs): 29.5  
 Power Line Size (AWG): #4 - 500MCM  
 Power Load Size (AWG): #4 - 500MCM  
 Control Wire Size (AWG): #12 - #16  
 Thermal Overload Type: Motor Logic Solid State  
 Thermal Overload Trip Class: Class 10/20 Selectable  
 Mounting: Panel

**Specification:**  
 Description: TeSys N Sz 5 open starter, 3 pole, 208 VAC  
 Type: FVNR  
 Voltages Code: L7 at 208Vac  
 Control Type: Common control  
 Coil Consumption: Inrush 650 VA  
 Sealed 10 VA

Three Phase			
200V	230V	460V	575V
75 HP	100 HP	200 HP	200 HP