



Note:

- Drawings Not To Scale
- Drawings Subject to Change Without Notice
- Dimensions are inches next to [Millimeters]

Part No.:

XBTGT4230



Schneider Electric United States
 North American Division
 Boston One Campus
 800 Federal Street
 Andover, MA 01810, USA
 Phone: +1 8773425173
 Email: CCC@us.schneider-electric.com

Technical Information:

North America Certifications:	UL 508, UL 1604, CSA C22-2 no. 14
IEC, CE Certifications:	EN 61131-2, IEC 61000-6-2, CE
FCC & EMC:	FCC (Class A), C-Tick
Applicable Machine Safety Std.:	Class 1 Div 2 T4A or T5 (UL and CSA), ATEX Zone 2/22
Marine Certifications:	ABS, BV, DNV, GL, LR, RINA, RMRS, RRR
Other Certifications:	ACA, GOST
Common Automation Protocols:	Modbus, Uni-TE, Modbus TCP/IP, FIPWAY, FIPIO, Modbus Plus
Other Protocols:	PacDrive, Siemens, Omron, Mitsubishi, Rockwell
Operating Temperature Range:	0c to 50c
Storage Temperature Range:	-20c to +60c
Relative Humidity"	0 to 90% non condensing

Specification:

Description:	4k Color STN
Screen Type:	640 x 480 pixels (VGA), 167 cd/m2
Resolution:	SUB-D9 (RS 232C/RS 422/485 serial link), RJ45 (RS485)
Interface Ports:	Ethernet IEEE 802.3 10/100 Base-T (RJ 45)
Ethernet Ports:	Type A (V1.1)
USB Ports:	1 audio out, 1 discrete in, 3 discrete out
Operating System:	IP65, NEMA 4X indoor
Enclosure Rating:	266 Mhz RISC
Processor:	512k
SRAM:	32M EPROM
Storage:	24 VDC
Supply Voltage:	