



SKiM® 93

Trench IGBT Modules


SKiM609GAR12E4

Features

- IGBT 4 Trench Gate Technology
- Solderless sinter technology
- $V_{CE(sat)}$ with positive temperature coefficient
- Low inductance case
- Isolated by Al₂O₃ DCB (Direct Copper Bonded) ceramic substrate
- Pressure contact technology for thermal contacts and electrical contacts
- High short circuit capability, self limiting to 6 x I_C
- Integrated temperature sensor

Typical Applications*

- Automotive inverter
- High reliability AC inverter wind
- High reliability AC inverter drives



GAR

Absolute Maximum Ratings				
Symbol	Conditions		Values	Unit
IGBT				
V _{CEs}			1200	V
I _C	T _j = 175 °C	T _s = 25 °C	748	A
		T _s = 70 °C	608	A
I _{Cnom}			600	A
I _{CRM}	I _{CRM} = 3xI _{Cnom}		1800	A
V _{GES}			-20 ... 20	V
t _{psc}	V _{CC} = 800 V	T _j = 150 °C	10	μs
	V _{GE} ≤ 15 V			
	V _{CEs} ≤ 1200 V			
T _j			-40 ... 175	°C
Inverse diode				
I _F	T _j = 175 °C	T _s = 25 °C	139	A
		T _s = 70 °C	110	A
I _{Fnom}			600	A
I _{FRM}	I _{FRM} = 3xI _{Fnom}		1800	A
I _{FSM}	t _p = 10 ms, sin 180°, T _j = 25 °C		900	A
T _j			-40 ... 175	°C
Freewheeling diode				
I _F	T _j = 175 °C	T _s = 25 °C	1397	A
		T _s = 70 °C	1107	A
I _{Fnom}			1350	A
I _{FRM}	I _{FRM} = 3xI _{Fnom}		4050	A
I _{FSM}	t _p = 10 ms, sin 180°, T _j = 25 °C		6480	A
T _j			-40 ... 175	°C
Module				
I _{t(RMS)}	T _{terminal} = 80 °C		700	A
T _{stg}			-40 ... 125	°C
V _{isol}	AC sinus 50 Hz, t = 1 min		2500	V

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
IGBT						
V _{CE(sat)}	I _C = 600 A	V _{GE} = 15 V chipelevel	T _j = 25 °C	1.85	2.10	V
			T _j = 150 °C	2.25	2.45	V
V _{CE0}			T _j = 25 °C	0.8	0.9	V
			T _j = 150 °C	0.7	0.8	V
r _{CE}	V _{GE} = 15 V		T _j = 25 °C	1.8	2.0	mΩ
			T _j = 150 °C	2.6	2.8	mΩ
V _{GE(th)}	V _{GE} = V _{CE} , I _C = 24 mA		5	5.8	6.5	V
I _{CES}	V _{GE} = 0 V	V _{CE} = 1200 V	T _j = 25 °C	0.1	0.3	mA
			T _j = 150 °C			mA
C _{ies}	V _{CE} = 25 V	V _{GE} = 0 V	f = 1 MHz	35.20		nF
C _{oes}			f = 1 MHz	2.32		nF
C _{res}			f = 1 MHz	1.88		nF
Q _G	V _{GE} = - 8 V...+ 15 V			3400		nC
R _{Gint}	T _j = 25 °C			1.3		Ω



SKiM® 93

Trench IGBT Modules

SKiM609GAR12E4


Features

- IGBT 4 Trench Gate Technology
- Solderless sinter technology
- $V_{CE(sat)}$ with positive temperature coefficient
- Low inductance case
- Isolated by Al_2O_3 DCB (Direct Copper Bonded) ceramic substrate
- Pressure contact technology for thermal contacts and electrical contacts
- High short circuit capability, self limiting to $6 \times I_C$
- Integrated temperature sensor

Typical Applications*

- Automotive inverter
- High reliability AC inverter wind
- High reliability AC inverter drives

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
$t_{d(on)}$	$V_{CC} = 600\text{ V}$	$T_j = 150\text{ °C}$		150		ns
t_r	$I_C = 600\text{ A}$	$T_j = 150\text{ °C}$		121		ns
E_{on}	$V_{GE} = 15\text{ V}$	$T_j = 150\text{ °C}$		136		mJ
$t_{d(off)}$	$R_{G\ on} = 4.1\ \Omega$	$T_j = 150\text{ °C}$		808		ns
t_f	$R_{G\ off} = 4.1\ \Omega$	$T_j = 150\text{ °C}$		100		ns
E_{off}	$di/dt_{on} = 5000\text{ A}/\mu\text{s}$	$T_j = 150\text{ °C}$		83		mJ
E_{off}	$di/dt_{off} = 4400\text{ A}/\mu\text{s}$	$T_j = 150\text{ °C}$		83		mJ
$R_{th(j-s)}$	per IGBT				0.068	K/W
Inverse diode						
$V_F = V_{EC}$	$I_F = 150\text{ A}$	$T_j = 25\text{ °C}$		2.1	2.5	V
	$V_{GE} = 0\text{ V}$	$T_j = 150\text{ °C}$		2.1	2.4	V
	chip					
V_{F0}		$T_j = 25\text{ °C}$	1.1	1.3	1.5	V
		$T_j = 150\text{ °C}$	0.7	0.9	1.1	V
r_F		$T_j = 25\text{ °C}$	4.3	5.6	6.4	m Ω
		$T_j = 150\text{ °C}$	6.7	7.8	8.5	m Ω
I_{RRM}	$I_F = 150\text{ A}$	$T_j = 150\text{ °C}$		153		A
Q_{rr}	$di/dt_{off} = 3300\text{ A}/\mu\text{s}$	$T_j = 150\text{ °C}$		15		μC
E_{rr}	$V_{GE} = -15\text{ V}$	$T_j = 150\text{ °C}$		9		mJ
E_{rr}	$V_{CC} = 600\text{ V}$	$T_j = 150\text{ °C}$		9		mJ
$R_{th(j-s)}$	per diode				0.501	K/W
Freewheeling diode						
$V_F = V_{EC}$	$I_F = 600\text{ A}$	$T_j = 25\text{ °C}$		1.7	1.9	V
	$V_{GE} = 0\text{ V}$	$T_j = 150\text{ °C}$		1.4	1.7	V
	chip					
V_{F0}		$T_j = 25\text{ °C}$	1.1	1.3	1.5	V
		$T_j = 150\text{ °C}$	0.7	0.9	1.1	V
r_F		$T_j = 25\text{ °C}$	0.5	0.6	0.7	m Ω
		$T_j = 150\text{ °C}$	0.7	0.9	0.9	m Ω
I_{RRM}	$I_F = 600\text{ A}$	$T_j = 150\text{ °C}$		510		A
Q_{rr}	$di/dt_{off} = 5300\text{ A}/\mu\text{s}$	$T_j = 150\text{ °C}$		123		μC
E_{rr}	$V_{GE} = -15\text{ V}$	$T_j = 150\text{ °C}$		39		mJ
E_{rr}	$V_{CC} = 600\text{ V}$	$T_j = 150\text{ °C}$		39		mJ
$R_{th(j-s)}$	per diode				0.048	K/W
Module						
L_{CE}				10	15	nH
R_{CC+EE}	terminal-chip	$T_s = 25\text{ °C}$		0.3		m Ω
		$T_s = 125\text{ °C}$		0.5		m Ω
w				1042		g
Temperatur Sensor						
R_{100}	$T_{Sensor} = 100\text{ °C}$ ($R_{25} = 5\text{ k}\Omega$)			339		Ω
$B_{100/125}$	$R_{(T)} = R_{100} \exp[B_{100/125}(1/T - 1/373)]$; $T[K]$;			4096		K



GAR




Fig. 1: Typ. output characteristic, inclusive $R_{CC'+EE'}$




Fig. 2: Rated current vs. temperature $I_C = f(T_C)$




Fig. 3: Typ. turn-on /-off energy = $f(I_C)$




Fig. 4: Typ. turn-on /-off energy = $f(R_G)$




Fig. 5: Typ. transfer characteristic




Fig. 6: Typ. gate charge characteristic




Fig. 7: Typ. switching times vs. I_C




Fig. 8: Typ. switching times vs. gate resistor R_G




Fig. 9: Typ. transient thermal impedance




Fig. 10: Typ. CAL diode forward charact., incl. $R_{CC'+EE}$




Fig. 11: Typ. CAL diode peak reverse recovery current





Fig. 12: Typ. CAL diode recovery charge

SKiM609GAR12E4




* all pos. dimensions valid when mounted

⊕ Ø 0,9 A B C


** valid for the outer 4 inserts

General Tolerances DIN ISO 2768-m
PCB spring landing pad = Ø 3,5 ± 0,2


A-A (2 : 1)
(12x screw hole)



B-B (2 : 1)
(2x guide ring)



SKIM 93



GAR

This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, Chapter IX

* The specifications of our components may not be considered as an assurance of component characteristics. Components have to be tested for the respective application. Adjustments may be necessary. The use of SEMIKRON products in life support appliances and systems is subject to prior specification and written approval by SEMIKRON. We therefore strongly recommend prior consultation of our staff.